

ReddiSpace

Acoustic Booths



View AR and 3D visual tools, statement of line and more at:
FRIANT.COM

FRIANT



FRÍANT



ReddiSpace **QuickTime**



ReddiSpace **QuickTime**



ReddiSpace **MeTime**



ReddiSpace **MeTime**



ReddiSpace **WeTime**



ReddiSpace **OurTime**



ReddiSpace





ReddiSpace



Introducing ReddiSpace, the ultimate solution for a private and focused environment. Our premium acoustic booth combines functionality and style for an enhanced productive workspace. For moments you need a quiet space to concentrate and minimize distractions, **ReddiSpace is ready.**

Soundproofing

Designed with exceptional soundproofing performance, providing a private and distraction-free environment that allows users to focus, communicate, and work without interruptions from external noise.



Adaptability

Equipped with a convenient work surface, lighting, and plug-and-play power, ReddiSpace is highly adaptable in any setting. With casters, these booths are mobile, allowing you to easily move and place them in different locations within your workspace as needed.



Customization

ReddiSpace offers customizable configurations in size, finish, and materials, allowing you to create a modern and professional look that complements your brand's identity. Customize and design a cohesive and polished aesthetic in your workspace that reflects your unique style.













UL Certified

ReddiSpace has undergone rigorous testing and complies with industry standards. Engineered with stability and security in mind, ReddiSpace is UL certified, meeting recognized safety requirements and providing a safe and comfortable station for your work environment.



Finishes









Interior (Acoustical PET)

							
18 Grey	03 Lt Grey	22 Taupe	27 Sky	08 Lilac	26 Eggplant	46 Ivy	05 Lake
							
06 Tangerine	12 Avocado	15 Lime	14 Café				








Top Finish (Worksurfaces)

			
CW White	BU Black	938 California Walnut	699 Rift


Fabric (Sofas)

							
1333 Grey	1300 Tan	1302 Sunshine	1313 Periwinkle	1320 Mauve	1321 Sunset	1309 Moss	1318 Ocean

Carpet

						
GR Grey	GB Grey Blue	AS Ash	GN Green	YL Yellow	GP Graphite	CH Charcoal

Casing

		
CW White	BU Black	8180 Oak

ReddiSpace Specifications



QuickTime



MeTime



WeTime



OurTime

Exterior Dimensions

40.5" x 40.5" x 86.5"

Power

1 Plug, 1 USB-A, 1 USB-C

Ventilation

2 Fans
Airflow: 1340 L/min
Air replaced every 1.2 min

Lighting

Sensor

Exterior Dimensions

63.5" x 47" x 86.5"

Power

2 Plugs, 1 USB-A, 1 USB-C

Ventilation

2 Fans
Airflow: 1340 L/min
Air replaced every 1.2 min

Lighting

Sensor

Exterior Dimensions

86.5" x 47" x 86.5"

Power

2 Plugs, 1 USB-A, 1 USB-C

Ventilation

4 Fans
Airflow: 2680 L/min
Air replaced every 1.8 min

Lighting

Manual

Exterior Dimensions

86.5" x 59" x 86.5"

Power

4 Plugs, 2 USB-A, 2 USB-C

Ventilation

8 Fans
Airflow: 4020 L/min
Air replaced every 1.6 min

Lighting

Manual

Materials

Casing

Layered composition of sheet metal, fire-rated gypsum board, recycled acoustic foam and acoustic felt

Glass

10mm tempered glass with aluminum frame

Exterior

Painted sheet metal or wood veneer



Frames

Aluminum

Door

6mm tempered glass with black painted aluminum frame

Carpet

Anti-static, stain resistant low loop pile carpet

Reddispace Specifications



UL	UL Listing	UL962
EMISSIONS	Indoor Air	ISO 16000-3:2011
FIRE RESISTANCE	Fire Resistance Testing	EN 1363-1:2020 UL723
NOISE TRANSMISSION	NIC	30dB
POWER	Infeed	Single-circuit plug and play 10' cord
	Interior Controls	Lights and ventilation fan are motion sensor activated
	Power	S: (2) outlets, (1) USB-A, (1) USB-C W: (4) outlets, (2) USB-A, (2) USB-C M: (4) outlets, (2) USB-A, (2) USB-C L: (4) outlets, (2) USB-A, (2) USB-C
	Fan air exchange	S (2 fans): air flow is 1340L/minute; Air Replaced every 1.2 minutes. W (2 fans): air flow is 5160L/minute; Air Replaced every 0.80 minutes. M (4 fans) : air flow is 2680L/minute; Air Replaced every 1.8 minutes. L (6 fans): air flow is 4020L/minute; Air Replaced every 1.6 minutes.
	Lighting	S: LED light 4W 4000K W: LED light 4W 4000K M: LED light 6W 4000K L: LED light 6W 4000K
TITLE 24	Lights	Motion sensor included
CONSTRUCTION	Exterior	1.0mm galvanized steel with powder coating or PVC surface
	Interior	9mm acoustic panel
	Front and Back	10mm safety glass, with aluminum frame
	Door	6mm safety glass, 45mm thick hidden frame door with stainless steel hinges

Please note that the images shown in this catalog are for reference purposes only. The actual product may differ in appearance, features, or specifications. For the most current information, please view the product price book at friant.com.



FRÍANT

View AR and 3D visual tools, statement of line and more at:

FRIANT.COM